

WHERE IT ALL BEGAN

3/4" RIM PANIC SOLUTION



4800 Series

The 4800

- For use with surface mounted rim exit devices with up to 1" throw. For use in new or replacement installations in wood or metal door frames and tight installs.
- No cutting of the frame
- Comes with Trines Patented 4-Pin Anchoring System for strength and stability. (See page 18 for details)
- Cavity is completely open – which means the 4800 allows for an incremental depth up to a 1" throw – **Competitor back plates do not allow for this versatility.**
- Built-in electronics automatically allow 11 through 28 AC and DC Voltage input – with surge and kickback protection.
- Contains a one piece locking mechanism with one solenoid.
Less parts mean less problems.
- Fail-safe/Fail-secure Field selectable.
- BHMA Grade 1 Electric Strike:
 - + 1,500,000+ Life cycles
 - + 3,000+ lbs. Holding Force.



Electronics allow for PLUG and PLAY capability

Electric Characteristics

Voltage	Pull In/Hold Amps	Duty	Sound
12DC	0.566/0.217	Intm./Cont.	Silent
24DC	0.253/0.099	Intm./Cont.	Silent
12AC	0.509/0.181	Intm./Cont.	Silent
16AC	0.405/0.149	Intm./Cont.	Silent
24AC	0.215/0.087	Intm./Cont.	Silent

4800-32D (Satin Stainless Steel – BHMA630)

The following finishes are:

- **4800-US3** (Bright Brass – BHMA605)
- **4800-US4** (Satin Brass – BHMA606)
- **4800-US10** (Satin Bronze – BHMA612)
- **4800-US10B** (Dark Bronze – BHMA613)
- **4800-32** (Polished Stainless Steel – BHMA629)

See Page 18 for options.

We challenge you to compare our strike against the competition on reliability, adaptability, and price!

