

AL624ET

Linear Power Supply/Charger Kit

Description

Altronix AL624ET power supply/charger kit converts a 115VAC 60Hz input into 12VDC output. This general purpose power supply has a wide range of applications for access control, security, and CCTV system accessories that require additional power.



AL624ET

Specifications

Input

Voltage 115VAC, 60 Hz, 1.2A.

Output

Voltage 12VDC.

Current 1.2A supply current.

Other Short circuit and thermal overload protection.
Filtered and regulated.

Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

Indicators (LED)

Input Input voltage is present.

DC Output Powered.

Physical and Environmental

Enclosure Dimensions (H x W x D)

8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm).

Enclosure accommodates two (2) 12VDC/4AH batteries
or one (1) 12VDC/7AH battery.

Product Weight 4.6 lbs. (2.1 kg).

Shipping Weight 5.15 lbs. (2.3 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 7 BTU/Hr.

Mounting hardware included.