

Model APS-300

Dual-Voltage Access Control Power Supply



Specifications

- Universal AC input 110 to 240 VAC
- 3A at 12 VDC, 1.5A at 24 VDC
- Cabinet size: 14" L x 8-1/2" W x 3-1/2" D
- Form C relay contacts, (SPDT), indicates AC power status
- ULC listed to ULC-S318 (Canada)
- UL listed to UL 294 and UL 603
- Battery always online, no voltage drop or switch over when AC fails
- Reverse battery protection, battery disconnect when battery is drained
- Operates under brownout conditions
- AC and DC power indicator LEDs
- Outputs are power limited
- Cabinet includes normally-open tamper switch and camlock

Features

- Sufficient power to support up to three magnetic locks or electric strikes plus required exit devices
- One Class 2 power limited output with thermal protection
- Precise battery regulation for all sealed lead acid batteries
- Input and output surge protection

Certifications & Listings

- UL 294 listed
- UL 603 recognized component
- CAN/ULC-S319 listed

Models

APS-300

Power Supply 12 or 24V 3/1.5A with Cabinet 14" x 9" x 3-1/2" Supervised Battery Charge

APS-3004C

APS-300 Power Supply in 14" x 9" Enclosure with 4 Outputs

APS-300FT

APS-300 Power Supply in 14" x 9" Enclosure with EOL Fire Relay

ALARMCONTROLS



ASSA ABLOY