# Securitron<sup>®</sup> BPS Linear Power Supply





Safe for use with readers, electric strikes, and maglocks, these units interface to fire alarm systems and provide battery backup. The Securitron BPS power supplies provide 12 VDC or 24 VDC output with a variety of amp sizes that support small or large power needs.

# **Features**

#### **Standard Features**

- 1, 4 or 8 outputs protected with polyswitch (PTC) 2 A circuit breakers
- LEDs provide an easy-to-read voltage indicator for output zone status (voltage, no voltage)
- Slide switches connect or disconnect load from power (excludes 1 A)
- Battery charging and backup capability (battery sold separately)
- Rugged steel enclosure
- Fire alarm relay connection for release of all devices upon fire alarm activation
- Clean linear power for flawless operation with all sensitive active electronic components
- MagnaCare® lifetime replacement, no-fault, no questions asked warranty



### Securitron BPS Linear Power Supply

# **Specifications**

#### Certifications

- UL 294 Listed
- CSA-C22.2 No.205 Listed
- MEA—City of New York Approved

#### **Electrical**

Input Voltage: 120 VAC

#### **Environmental**

 Operating Temperature: 32° to 105° F [0 to 40° C]

#### **Shipping Weight**

- BPS-12-1, BPS-24-1: 9 lbs [4.08kg]
- BPS-12-3, BPS-24-2: 15 lbs [6.80kg]
- BPS-12-45, BPS-24-3: 18 lbs [8.16kg]
- BPS-12-6, BPS-24-4: 24 lbs [10.89kg]
- BPS-12-9, BPS-24-6: 28 lbs [12.70kg]
- BPS-12-15, BPS-24-10: 33 lbs [14.97kg]

## **Dimensions**

12 VDC	CAPACITY	24 VDC	CAPACITY	CABINET SIZE	OUTPUTS
BPS-12-1	1A	BPS-24-1	1A	12" x 9" x 4" [305mm x 229mm x 102mm]	1
BPS-12-3	3 A	BPS-24-2	2A	14" x 14" x 4" [305mm x 356mm x 102mm]	4
BPS-12-45	4.5 A	BPS-24-3	3 A	14" x 14" x 4" [305mm x 356mm x 102mm]	4
BPS-12-6	6 A	BPS-24-4	4A	15" x 18" x 6" [381mm x 457mm x 152mm]	8
BPS-12-9	9 A	BPS-24-6	6A	15" x 18" x 6" [381mm x 457mm x 152mm]	8
BPS-12-15	15 A	BPS-24-10	10 A	15"x 18"x 6" [381mm x 457mm x 152mm]	8

# How to Order

MODEL SERIES	MONITORING OPTIONS	VOLTAGE	OUTPUT POWER	
BPS	M	<b>- 24</b>	-X	
BPS	(blank) No Monitoring	<b>12</b> 12 VDC	X Output in Amps	
	M PSM Monitoring	24 24 VDC		