



# Models EXP-1, EXP-2, EXP-15, EXP-25

## Explosion Proof Momentary Contacts

### Models

**EXP-1**  
N/O & N/C Momentary Switch,  
CLASS I & II, Division I & II, GROUP  
B, C, D, E, F & G, NEMA 7 & 8

**EXP-15**  
Momentary Action Panic

**EXP-2**  
N/O & N/C Latching Switch, CLASS  
I & II, Division I & II, GROUP B, C,  
D, E, F & G, NEMA 7 & 8

**EXP-25**  
Latching Action Panic

### Specifications

- Heavy cast NEMA type 7 enclosure
- Conforms to Class I, DIV. I and II, Group B, C, D, E, F and G
- One normally-open and normally-closed contact
- Contact rated 5A at 35 VDC or 120 VAC
- Pipe thread 1/2-14 NPT
- Size: 4" x 6-1/2" x 4-1/2"
- UL and ULC approved for hazardous locations

### Features

- Designed for hazardous locations
- 2" push button silkscreened with black epoxy ink
- Latching action switch, labeled "PANIC"

### Options

- Momentary action switch, labeled "PUSH TO EXIT"
- Latching action switch, labeled "PUSH TO EXIT"
- Momentary action switch, labeled "PANIC"
- Latching action switch, labeled "PANIC"
- Push button can be customized

# ALARM CONTROLS



ASSA ABLOY