



LISTED

ISSUE # U-557

DOOR HOLDER FOR USE IN HAZARDOUS LOCATIONS Class 1 Div 2

**ASTERIX SECURITY HARDWARE INTERNATIONAL INC
MISSISSAUGA, ONTARIO**

24 VOLTS D.C. 0.25 AMP 6.0 WATTS
OPERATING TEMPERATURE 85 DEGREE CENTIGRADE
MAXIMUM AMBIANT TEMPERATURE 40 DEGREE CENTIGRADE
FOR SUPPLY CONNECTIONS USE 75 DEGREE CENTIGRADE WIRE
THIS UNIT MAY BE USED IN THE FOLLOWING ATMOSPHERE:
ACETON, AMMONIUM HYDROXIDE, ASTM FUEL C. BENZENE,
METHYL ETHYL KETONE, DIETHYL ETHER, 2-NITROPROPANE,
ETHYL ACETATE, FURFURAL, NORMAL HEZANE, METHYL
ALCOHOL

CAUTION:

TO REDUCE THE RISK OF IGNITION OF HAZARDOUS ATMOSPHERES,
DISCONNECT THE DOOR HOLDER FROM THE SUPPLY CIRCUIT BEFORE
OPENING. KEEP TIGHTLY CLOSED WHEN IN OPERATION.
TO REDUCE RISK OF FIRE OR EXPLOSION, DO NOT INSTALL WHERE THE
MARKED OPERATION TEMPERATURE EXCEEDS IGNITION TEMPERATURE
OF HAZARDOUS ATMOSPHERES.
UNIT MUST BE CONNECTED TO A N.E.C. CLASS 2 SUPPLY CIRCUIT
MAGNETIC LOCK : 17XHD SERIES