

STANDARD FEATURES

Actuation: 1/8" total bar movement for mechanical switch actuation

Contact: SPDT, 5 Amp @ 30VDC (2nd switch optional) Accessories include: PT-2U Power Transfer Loop

Standard length, 36"

MODEL	FINISH	LIST PRICE
MSB550V	628 Aluminum Anodized	232.00
MSB550Y	335 Black Anodized	240.00
MSB550S	629 Bright Stainless Steel	385.00
MSB550U	630 Brushed Stainless Steel	385.00

2 SPDT Contacts

Add "2" for 2nd mechanical switch for dual-failsafe redundant operation; alarm shunt; or monitoring output. Ex: MSB550-2V

Bars for wide doors

42 Bar for 42" Door. May be field cut.	N/C
48 Bar for 48" Door. May be field cut	N/C
Fx: MSB550V42	

EXIT MECHANICAL SWITCH - OUTDOOR WEATHER RESISTANCE



ADD 31.00

PUSH TO EXIT Field Applied Sign with green letters

STANDARD FEATURES

OUTDOOR, WEATHER RESISTANCE

Water Sealed Switches

Actuation: 1/8" total bar movement for mechanical switch actuation

Contact: SPDT, 5 Amp @ 30VDC (2nd switch included) Accessories include: PT-3V Power Transfer Loop, 2 SPDT

Contacts included

Standard length, 36"

MODEL	FINISH	LIST PRICE
MSB550-2VW	628 Aluminum Anodized	374.00
MSB550-2YW	335 Black Anodized	374.00

Bars for wide doors

42 Bar for 42" Door. May be field cut.	N/C
48 Bar for 48" Door. May be field cut	N/C
Ev: MSB550-2\/\\/\/2	