

ELECTROMAGNETIC LOCKS

▶ A LARGE RANGE OF ELECTROMAGNETIC LOCKS SUITABLE FOR ALL YOUR NEEDS

660 - 880 - 1100

Illuminated surface mount electromagnetic locks



**With Built-In Time Adjustable
433 MHz Receiver**



MAGLOC660

660 LB



MAGLOC880

880 LB



MAGLOC1100

1100 LB



The new range of electromagnetic locks with feedback in 660, 880 and 1100 lb versions, complies with the "disability act" regulation.

- **Request to exit input on board.**
- **Accepts up to 40 transmitters.**
- **Unlock time from 1-10 seconds.**
- **NF S 61-937.**
- **Surface mount.**
- **Relay/Monitored:** Relay + Lock status (According to model).
- **High resistance to corrosion.**
- **No mechanical wear.**
- **Easy installation.**
- **Recommended for indoor use.**
- **Visual feedback.**
- **No residual magnetism.**
- **Built-in varistor (Electronic protection to eliminate back EMF).**

- Electromagnetic lock dimensions (L x W x D):
 - MAGLOC660 = 9-3/4 x 1-3/4 x 1 inch,
 - MAGLOC880 = 10 x 2 x 1 inch,
 - MAGLOC1100 = 10-3/8 x 2-5/8 x 1-5/8 inch.
- Armature dimensions (L x W x D):
 - 660 lbs = 7-1/4 x 1-3/8 x 2/5 inch,
 - 880 lbs = 7-1/4 x 1-7/8 x 1/2 inch,
 - 1100 lbs = 7-1/4 x 2-3/8 x 3/8 inch.
- Silent operation.
- Optional: Electromagnetic lock accessories
- Input voltage: 12 VDC
- Consumption:
 - 12V dc = 550mA.

COLOR CODES:



RED LOCKED



GREEN OPEN



WEEE



IP42



CE Certification