

Part No.: R001008R

Applications:

This document establishes the specifications for a four conductor unshielded riser rated cable used for communication applications.

Construction Details:

Number of Conductors: 4/C Conductor: 18AWG Stranded bare copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.062 in. Color Code: Black, Red, White, Green Jacket Material: Polyvinyl Chloride Nominal Jacket Thickness: 0.015 in. Nominal Diameter: 0.180 in. Surface Print: 3122598 CMR 18AWG C(ETL)US FT4 A B C D E F 0 1 2 3 4 5 6 7 8 9 + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.


Technical Details:

Temperature Rating

	Operation:	-20°C to +60°C
Nominal Weight:		29 lbs. / 1,000 Feet

18-4 Unshielded Non-Plenum

ETL listed for guaranteed performance Made in the USA



Standards:

- NEC Article 800
- UL Subject 444, Type CMR FT4

Codes & Listings:

C(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 06/15 Revision: 3 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com



18-4 Unshielded Non-Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: R001008R

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to
this specification sheet and upon confirmation of your or-
der; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date:



Issue Date: 06/15 Revision: 3

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com