

Part No.: R0010186

Applications:

This document establishes the specifications for a six conductor unshielded riser rated cable used for communication applications.

Construction Details:

Number of Conductors: 6/C

Conductor: 18AWG Stranded bare copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.062 in.

Color Code: Black, Red, White, Green, Blue, Brown

Jacket Material: Polyvinyl Chloride Nominal Jacket Thickness: 0.015 in.

Nominal Diameter: 0.210 in.

Surface Print: 3122598 CMR 18AWG C(ETL)US FT4 A B C D E F 0 1 2 3 4 5 6 7 8 9 + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.


Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:	
Company:	
Date:	



ETL listed for guaranteed performance

Made in the USA



Technical Details:

Temperature Rating

Operation: $-20^{\circ}\text{C} \text{ to } +60^{\circ}\text{C}$

Nominal Weight: 42 lbs. / 1,000 Feet

Standards:

- NEC Article 800
- UL Subject 444, Type CMR FT4

Codes & Listings:

• C(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Issue Date: 02/14 Revision: 0 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.