

**RB7**

## Ultra Sensitive Relay Module

Altronix RB7 Multiple Relay Module incorporates seven (7) isolated form “C” relay outputs which can be activated via positive (+) low current trigger inputs. Typical applications include the switching of alarm devices (e.g. annunciator, signals, etc.) from PGM outputs of alarm panels or from another source.



RB7

**Specifications**
**Input**

Voltage	12VDC or 24VDC operation
Current Draw	120mA

**Contact Rating**

Seven (7) isolated form “C” 1A/120VAC or 28VDC contacts  
 Seven (7) independent (3VDC to 24VDC@ 2mA minimum)  
 positive (+) triggers.

**Indicators (LED)**

Trigger	Seven (7) individual trigger LEDs
---------	-----------------------------------

**Physical and Environmental**
**Dimensions (L x W x H)**

6.5” x 3.25” x 1” (165.1mm x 82.55mm x 25.4mm)

**Product Weight** 0.15 lb. (0.06 kg)

**Shipping Weight** 0.25 lb. (0.11 kg)

**Temperature**

**Operating** -25°C to 55°C (-13°F to 131°F)

**Storage** -25°C to 70°C (-13°F to 158°F)

**Relative Humidity** 85% +/-5%

**Lifetime Warranty**