



Model TS-25

Emergency Door Release

Specifications

- SPDT latching push button
- Contacts rated 3A at 35 VDC or 120 VAC
- Switch operates on 12 or 24 VAC or VDC
- 12 or 24 VDC operation

Features

- 5/8" x 7/8" red rectangular push button; Switch mounted on either narrow or single gang wall plate.
- Plate labeled "EMERGENCY DOOR RELEASE ALARM WILL SOUND"
- Switch illuminated with high-brightness LED
- Switch terminated with colored leads
- 85 dB Piezo buzzer

Options

- 430 stainless steel wall plate
- 1-3/4" narrow 302 stainless steel wall plate
- Other wall plate finishes are available
- Push button labeled "PUSH"
- Push button labeled "EXIT"
- Model TS-26 is narrow and TS-25 is single gang wall plate

Models

TS-25

SPDT 3A Illuminated Alternate Action Push Button, with Buzzer, "EMERGENCY DOOR RELEASE ALARM WILL SOUND", Mounted on Single Gang Stainless Steel Plate

TS-26

SPDT 3A Illuminated Alternate Action Push Button, with Buzzer, "EMERGENCY DOOR RELEASE ALARM WILL SOUND", Mounted on 1-3/4" Stainless Steel Plate

ALARM CONTROLS



ASSA ABLOY