

RT Series

Wireless Transmitters



Wireless remote transmitters allow access control for up to three doors from one device. Ideal for front desk/reception applications or hard-to-wire locations. Designed to work with magnetic locks, electric strikes, keypads, gate operators and door operators. Kits include channel receiver and transmitter with mount and keychain.

Features

Standard Features

- Transmitter can be mounted under a desk or on a wall
- 12" antenna with up to 300' range
- Rolling code with over 1 billion code combinations
- Latching option keeps doors unlocked until button is pressed again
- Receiver can be controlled by up to 30 transmitters
- Receiver has a 5 second momentary output

Options

- **RT-1** one receiver, two transmitters
- **RT-1T** additional transmitter
- **RT-1TW** additional transmitter with wire lead
- **RT-3** three receivers, one transmitter
- **RT-3R** additional receiver

Specifications

Certifications & Listings

- CE Certified
- RoHS compliant

Dimensions

- 2-1/2"L x 1-1/4"W x 3/4"D

Electrical

- Receiver operates on 12 or 24 VDC/VAC
- Max current draw 50mA
- Relay SPDT contact rated 1A at 30 VDC or 120 VAC
- Working frequency: 433.92 MHz

Operating Temperature

- -4 to +140F

TS-34 Series

Mounted Wall Buzzers



Audible buzzer station for mounting on single gang or narrow wall plate

Features

Standard Features

- Buzzer mounted on wall plate with stainless steel finish
- Sound level 85db at 3ft

Options

- **TS-34** mounted on single gang wall plate with 430 stainless steel finish
- **TS-34N** mounted on narrow wall plate with 302 stainless steel
- Finishes: multiple plate options available
- Custom screening available

Specifications

Certifications & Listings

- CE Certified
- RoHS compliant

Electrical

- Operates on 3 to 28 VDC
- 6" red and black leads

TS-41

Mounted Wall Buzzer



Sonalert buzzer mounted on single gang wall plate

Features

Standard Features

- Buzzer mounted on single gang wall plate with stainless steel finish
- Sound level 85db at 3ft

Options

- Finishes: multiple plate options available
- Custom screening available
- **SCVC** volume control

Specifications

Electrical

- Current draw 3mA at 6VDC, 18mA at 28 VDC
- 6" red and black leads
- Screw terminals