





## **FEATURES**

**WPT Wireless Electric Power Transfer Device** 

- Output: 600 mA @12VDC/ 300 mA @24VDC
- Max Input: 600 mA @24VDC
- Max Door Gap: Horizontal < 5/64" (2mm) Vertical < 5/64" (2mm) with door gap 3/16" (5mm)
- LED on Frame & Door side
- UL 1034 and UL 10C 3 hrs fire-rated, FCC Part 15 Compliant

**WPT** Wireless Power Transfer Device 450.00

## **Concealed Power Transfer Device**



LIST





PT-5 UL Listed Concealed Power Transfer Device, for use with all high and low current applications 65.00

Also recommended for use with Von Duprin\* EL 33 and 99 series and other high inrush devices \*Von Duprin is a registered trademark of Ingersol Rand and Von Duprin. Not intended as endorsement.

Power Transfer Loops			Distributor Discount Code	V	LIST
PT-2U	PT-3V	PT-2U	Armored flex conduit, less wires, 18" long, 1/4" I.D.		21.00
		PT-3V	Armored flex conduit, less wires, with wire junction box, 20" long, 1/4" I.D.		49.00
		PT-3/8V	Armored flex conduit, less wires, with wire junction box, 20" long, 3/8" I.D.		65.00

