





Polycarbonate Housing, Strato-Silver Edition incl. Stainless-Steel Faceplate • Surface-Mounted Designed, developed and made in Germany



GENERAL	
Housing	Polycarbonate, UV-resistant, incl. stainless-steel faceplate F101
Doorbell button	Stainless-steel button with illuminated LED ring
Mounting type	Surface-mounted
Power supply	15 V DC (power 110 - 240 VA C) or Power over Ethernet (PoE 802.3af Mode-A)
Weight	303 g
Connectors	Power, electric door opener/strike, door chime, door opener button, network
Weather protection	Yes, IP65
Approvals	CE, IC, FCC, IP65
Dimensions	157 x 75 x 35 mm (H x W x D) 6,18 x 2,95 x 1,38 in (H x W x D)
Operating conditions	-20 to +40°C / -4 to 104°F Humidity 10 to 85 % RH (non condensing)
Scope of delivery	Video Door Station, mounting plate, power supply unit (world-wide, 110 - 240 V), DIN-rail power supply sold separately, screw package, Quickstart Guide
EAN	4260423860193
Warranty	see www.doorbird.com/warranty

CURRENT SYSTEM REQUIREMENTS

Mobile device	Latest iOS on iPhone/iPad, latest Android on Smartphone/Tablet
Internet	High-Speed landline broadband internet connection, DSL, cabel or fiber, min. 500 kbs uploadbandwith, no socks- or proxyserver
Network	802.11 b/g/n 2.4 GHz or Ethernet network, with DHCP
Recommended installation	Camera lens should be at a min. height of 125 cm (49 in)

VIDEO	
Camera	HDTV 720 p, dynamic (VGA - HDTV)
Lens	High-end ultra wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened, IR-capable
Night-vision	Yes, light sensor, automatic IR-cut filter, 12 IR-LEDs

AUDIO

Audio components	Speaker and microphone, echo and noise cancellation
Audio streaming	Two-way duplex

NETWORK

WiFi Ethernet

Connector, PoE

802.11 b/g/n 2.4 GHz

MOTION SENSOR

Туре	Passive infrared sensor (PIR)
Detection angle	180°
Range	2 - 8 m (79 - 315 in) depends on environment

INTEGRATED WIRELESS MODULES

WiFi

2,4 GHz, internal antenna

OPTIONAL ACCESSORIES

Sold separately

see www.doorbird.com/buy