

MGT-2450P CLASS II POWER SUPPLY

24VAC 50VA Class II Power Supply

FEATURES

- Input: 120V 60Hz
- Output: 24VAC ~ 50VA
- Class II power supply
- Auto resetting fuse & 3rd ground prong
- Three screw terminal output
- Individually boxed
- UL and CUL listed
- LED AC power input indicator
- PTC fused



HOW TO ORDER

- **MGT-2450P**
24VAC 50VA Class II Power Supply

DESCRIPTION


The MGT2450P is a highly reliable plug-in Class II linear power supply providing 24VAC output at 50VA. It is built with a heavy duty case that includes a mounting tab and screw. An auto-resetting PTC fuse provides overload protection. An LED indicates AC power input. The plug includes a ground prong and there are three screw terminals for the output, including ground. The unit is UL cUL 1310 listed.

MGT-2450P CLASS II POWER SUPPLY

SPECIFICATIONS

- Input voltage: 120VAC 60Hz
- Rate current: 2000mA
- Output voltage: AC 24.0V +/- 5%
- No load voltage: AC 28.0VMax
- Exciting current (I_o): 140mA Max. at input 120VAC 60Hz without secondary load.
- Insulation test: 500 VDC 100MΩ Min. between input plug and output terminal and case.
- AC blade pull test: Pull AC blades by 35lb for one minute without pull out from the case.
- Temperature rise: Input 120VAC 60Hz with secondary load 2000mA, shall not exceed 40deg on case surface (By them 10meter) 75deg for primary winding (By resistance method). At ambient temp. 25°C
- Normal operating temperature at: -10°C ~ +40°C
- Storage temperature at: -20°C ~ +70°C
- Normal operating humidity at: 30% ----- 85% R.H.
- Net Weight (APPROX.): 715g.

ENCLOSURE DIMMENSIONS



COLOR	White
MATERIAL	ABS
UNIT	mm